

Terminations for steel wire ropes — Safety —

Part 2: Splicing of eyes for wire rope slings

The European Standard EN 13411-2:2001 has the status of a
British Standard

ICS 53.020.30; 77.140.99

National foreword

This British Standard is the official English language version of EN 13411-2:2001.

The UK participation in its preparation was entrusted to Technical Committee MHE/2, Wire ropes, which has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible European committee any enquiries on the interpretation, or proposals for change, and keep the UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

A list of organizations represented on this committee can be obtained on request to its secretary.

Cross-references

The British Standards which implement international or European publications referred to in this document may be found in the BSI Standards Catalogue under the section entitled “International Standards Correspondence Index”, or by using the “Find” facility of the BSI Standards Electronic Catalogue.

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

This British Standard, having been prepared under the direction of the Engineering Sector Committee, was published under the authority of the Standards Committee and comes into effect on 15 July 2001

Summary of pages

This document comprises a front cover, an inside front cover, the EN title page, pages 2 to 8, an inside back cover and a back cover.

The BSI copyright date displayed in this document indicates when the document was last issued.

Amendments issued since publication

Amd. No.	Date	Comments

English version

Terminations for steel wire ropes - Safety - Part 2: Splicing of eyes for wire rope slings

Terminaisons pour câbles en acier - Sécurité - Partie 2:
Epissures de boucles pour élingues en câble d'acier

Endverbindungen für Stahldrahtseile - Sicherheit - Teil 2:
Spleißen von Seilschlaufen für Anschlagseile

This European Standard was approved by CEN on 20 April 2001.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Contents	Page
Foreword	3
Introduction	4
1 Scope	4
2 Normative references	4
3 Terms and definitions	5
4 Hazards	5
5 Splicing operation	6
6 Verification of the safety requirements	6
Annex ZA (informative) Clauses of this document with EC Directives	7

Foreword

This European Standard has been prepared by Technical Committee CEN/TC 168 "Chains, ropes, webbing slings and accessories", the secretariat of which is held by BSI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by November 2001, and conflicting national standards shall be withdrawn at the latest by November 2001.

This European Standard has been prepared under a mandate given to CEN by the European Commission and the European Free trade Association, and supports essential requirements of EC Directive(s).

For the relationship with EC Directives, see informative annex ZA which is an integral part of this standard.

The other Parts of this European Standard are:

- Part 1: Thimbles for steel wire rope slings
- Part 3: Ferrules and ferrule-securing
- Part 4: Metal and resin socketing
- Part 5: U-bolt wire rope gripped termination
- Part 6: Asymmetric wedge socket
- Part 7: Symmetric wedge socket

This is the first edition of this part of this European Standard.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and the United Kingdom.

Introduction

This European Standard has been prepared to provide a means of conforming with the essential safety requirements of the Machinery Directive and associated EFTA Regulations.

The method of splicing described in the standard is based on historical experience and will produce a termination having an efficiency of at least 80%.

Purchasers ordering to this standards are advised to specify in their purchasing contract that the supplier operates a certified quality assurance system applicable to the relevant Part of this standard (eg EN ISO 9001) to ensure themselves that products claiming to comply consistently achieve the required level of quality.

While producing this standard it was assumed that negotiation occurs between the manufacturer and the user to decide whether a spliced eye is required.

1 Scope

This standard specifies minimum requirements for the splicing of eye terminations for six or eight strand steel wire ropes of up to 60 mm diameter complying with prEN 12385-4 used for slings to ensure that the spliced eye is strong enough to withstand a force of at least 80 % of the minimum breaking load of the rope.

Other hazards covered by this standard are identified in clause 4. Resistance to fatigue loading is not considered to be a significant hazard for slings and is not covered by this standard.

2 Normative references

This European Standard incorporates by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this European Standard only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies (including amendments).

EN 292-2 : 1991 +A1 : 1995	<i>Safety of machinery - Basic concepts - General principles of design Part 2: Technical principles and specifications (Amendment 1 : 1995)</i>
EN 1050:1996	<i>Safety of machinery - Principles for risk assessment acceptance</i>
prEN 12385-2	<i>Steel wire ropes – Safety - Part 2: Classification, designation and definitions</i>

3 Terms and definitions

For the purposes of this European Standard the terms and definitions given in prEN 12385-2 apply together with those given below.

3.1

spliced eye termination (hand-spliced)

loop or eye at the end of a rope made by tucking the ends of the strands back into the main body of the rope

3.2

load carrying tuck

single reeving of a strand that comes out of the rope, is passed over a strand, then passed under a strand or strands, and finally comes out of the rope

NOTE This definition excludes the start which is not considered to be load carrying.

3.3

splicer

person carrying out the splicing

3.4

competent person

designated person, suitably trained qualified by knowledge and practical experience, and with the necessary instruction to ensure that the required operations are correctly carried out

4 Hazards

This clause contains the hazards and hazardous situations, as far as they are dealt with in this European standard, identified by risk assessment significant for this type of machinery and which requires action to eliminate or reduce risk.

Accidental release of a load, or release of a load due to failure of the spliced eye terminations of a sling puts at risk, either directly or indirectly, the safety or health of those persons within the danger zone. The requirements of this standard ensure on the basis of historical experience that the breaking force of the splice will not be less than 80% of that of the rope.

Table 1 contains those hazards that require action to reduce risk identified by risk assessment as being specific and significant for spliced eye terminations.

Table 1 - Hazards and associated requirements

Hazards identified in annex A of EN 1050: 1996		Relevant clause of annex A of EN 292-2: 1991+A1: 1995	Relevant clause/ subclause of this standard
1.7	Puncture hazard	1.3	5

5 Splicing operation

5.1 General

Splicing shall be carried out by a splicer. The splicer shall be trained in splicing

5.2 Number of tucks required

For each strand, the splice shall have five series of load carrying tucks. At least three of the load carrying tucks shall be made with the whole strand, the remainder shall be made with strands comprising at least 50 % of the wires.

5.3 Direction of the load carrying tucks

Load carrying tucks shall be made against the lay of the rope.

5.4 Ropes with a steel wire rope core

Where the rope has a steel wire rope core, the core shall be unlaid at the end of the loop where splicing starts and be spliced with the outer strands for three tucks. The tail ends of the strand from the core shall not protrude from the splice.

5.5 Protruding wires

Any protruding wires must be addressed; for example by serving, reinsertion of the tails back into the rope, or by covering with heat shrink wrapping. Where used, serving or wrapping shall not cover the three full strand load carrying tucks.

6 Verification of the safety requirements

6.1 Qualification of personnel

Any person verifying the splice shall be a competent person.

6.2 Number of tucks

The requirements of 5.2 shall be confirmed by visual inspection.

6.3 Direction of the tucks

The direction of the tucks shall be confirmed by visual inspection.

6.4 Ropes with a steel wire rope core

The splice shall be visually inspected to ensure that the tails of the core do not protrude outside of the rope.

6.5 Protruding wires

The splice shall be visually inspected to ensure that the tails of the tucks do not protrude outside of the rope.

Annex ZA (informative)

Clauses of this document with EC Directives

This European Standard has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association and supports essential requirements of EC Directive :

Machinery Directive 98/37/EC, amended by Directive 98/79/EC.

Compliance with this standard provides one means of conforming with the specific essential requirements of the Directive concerned.

WARNING: Other requirements and other EC Directives may be applicable to the products falling within the scope of this standard.

Bibliography

- | | |
|--------------|--|
| prEN 12385-1 | Steel wire ropes – Safety - Part 1: General requirements and terms of acceptance |
| prEN 12385-4 | Steel wire ropes – Safety - Part 4: Stranded ropes for general applications |

BSI — British Standards Institution

BSI is the independent national body responsible for preparing British Standards. It presents the UK view on standards in Europe and at the international level. It is incorporated by Royal Charter.

Revisions

British Standards are updated by amendment or revision. Users of British Standards should make sure that they possess the latest amendments or editions.

It is the constant aim of BSI to improve the quality of our products and services. We would be grateful if anyone finding an inaccuracy or ambiguity while using this British Standard would inform the Secretary of the technical committee responsible, the identity of which can be found on the inside front cover. Tel: 020 8996 9000. Fax: 020 8996 7400.

BSI offers members an individual updating service called PLUS which ensures that subscribers automatically receive the latest editions of standards.

Buying standards

Orders for all BSI, international and foreign standards publications should be addressed to Customer Services. Tel: 020 8996 9001. Fax: 020 8996 7001. Standards are also available from the BSI website at <http://www.bsi-global.com>.

In response to orders for international standards, it is BSI policy to supply the BSI implementation of those that have been published as British Standards, unless otherwise requested.

Information on standards

BSI provides a wide range of information on national, European and international standards through its Library and its Technical Help to Exporters Service. Various BSI electronic information services are also available which give details on all its products and services. Contact the Information Centre. Tel: 020 8996 7111. Fax: 020 8996 7048.

Subscribing members of BSI are kept up to date with standards developments and receive substantial discounts on the purchase price of standards. For details of these and other benefits contact Membership Administration. Tel: 020 8996 7002. Fax: 020 8996 7001. Further information about BSI is available on the BSI website at <http://www.bsi-global.com>.

Copyright

Copyright subsists in all BSI publications. BSI also holds the copyright, in the UK, of the publications of the international standardization bodies. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI.

This does not preclude the free use, in the course of implementing the standard, of necessary details such as symbols, and size, type or grade designations. If these details are to be used for any other purpose than implementation then the prior written permission of BSI must be obtained.

If permission is granted, the terms may include royalty payments or a licensing agreement. Details and advice can be obtained from the Copyright Manager. Tel: 020 8996 7070.